MATERIAL SAFETY DATA SHEET

Page 1 of 2 Date: 12/04/02

Rev. 1

For Chemical Emergency Only Section 1

In the US & Canada (800) 424-9300 Pacer Technology 9420 Santa Anita Avenue Int'l & Wash DC (COLLECT) (202) 483-7616 Rancho Cucamonga, CA 91730 Telephone for Information (909) 987-0550

I. PRODUCT IDENTIFICATION: **Plastic Fusion - Part B: Activator**

II. COMPOSITION

INGREDIENTS	CONCENTRATION%	C.A.S.#	ACGIH TLV
Methyl methacrylate (MMA)*	60-85	80-62-6	100ppm
Acrylated copolymers	12-30	trade secret	
Amine condensate	0.5-5	trade secret	
Metal salt, acid complex solution	0.1-1	trade secret	

^{*}SARA Section 313 Toxic Chemicals

III. CHEMICAL AND PHYSICAL PROPERTIES

Vapor Pressure: 29mmHg @ 20C Vapor Density: Heavier than Air, 3.5 for MMA

Specific Gravity: Solubility in water: Insoluble 1.05

Boiling point: 214F for MMA Appearance: light gel, amber colored

Odor: pungent acrylic odor

IV. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flashpoint (T.C.C.): 51F Explosive Limits in air: Lower 2, Upper 12.5 for MMA

Recommended Extinguishing Agents: Water, dry chemical or carbon dioxide

Hazardous Products Formed by Fire or Thermal Decomposition: Toxic fumes of carbon oxides may evolve upon exposure to heat or open flame. Use self-contained breathing apparatus if burning.

Unusual Fire or Explosive Hazards: none Closed containers may burst when heated. Cool containers with water spray.

Compressed gases: none Solvents: none Pressure at 23C: N/A

V. REACTIVITY DATA

Stability: Stable Hazardous Polymerization: may occur

Hazardous Decomposition Products: oxides of carbon, acrid smoke

Incompatibility: oxidizers, heat, reducing agents, free radical generators, ignition sources, amines

VI. SPILL OR LEAK PROCEDURES

Remove sources of ignition. Use with ventilation. Dike area to prevent spreading. Absorb on vermiculite, sand or other inert absorbing material. Dispose of as a chemical waste in accordance with current local, state, and federal regulations. Do not discharge into water. Wash spill area with strong detergent. After proper mixing of resin and activator sides, the material will polymerize into a cured solid state which can be treated as a nonhazardous solid. Applicable CERCLA/RCRA waste code: 0001 (ignitability) U162 (MMA).

VII. STORAGE AND HANDLING PROCEDURES

Storage: Avoid storage over 100F, contamination with incompatible materials. Store in cool place away from direct sunlight.

Handling: Avoid prolonged or repeated breathing of vapor. Avoid contact with skin and eyes. Wash hands before smoking or eating.

VIII. SHIPPING REGULATIONS

DOT and IATA Hazard Classification:ORM-D in plastic containers or small volume cans, 1 gallon or less.

Proper DOT Shipping Name – bulk for containers over 1 gallon in volume: Adhesive containing flammable liquid, class 3, UN1133, PGII, flammable liquid label required.

IX. EMERGENCY TREATMENT

Eye Irritation: Immediately flush eyes with water for at least 15 minutes. Get medical attention. Skin Contact: Wash thoroughly with soap and water. Discard contaminated clothing. Do not use organic solvents on skin. For long term exposure or in case of irritation, get medical attention. Inhalation: Remove person to fresh air. Get medical attention if short of breathe or if respiratory symptoms develop.

Ingestion: Give 1-2 glasses of milk or water to conscious person. Do not induce vomiting. Get medical attention.

X. PERSONAL PROTECTION

Respiratory: Use proper positive airflow ventilation in work areas/explosion proof equipment in confined areas where vapors may exceed TLV limits.

Skin: Avoid skin contact, wear impervious gloves and protective clothing if in direct contact with material. Disposable polyethylene gloves with vinyl latex overgloves will give protection.

Eyes: Wear safety goggles or side shield safety glasses. Do not wear contact lenses.

XI. HEALTH HAZARD DATA

Hazard Categories: immediate X delayed X fire X pressure reactivity

Potential Routes of Entry: skin X inhalation X ingestion X

Symptoms of Overexposure: Possible skin and eye irritation on contact is likely. Vapor may irritate

throat.

Exposure limits: ACGIH OSHA OTHER

Ingredients

Methyl Methacrylate 100ppm 100ppm 100ppm Canada

Target organs Carcinogen

NTP IARC OSHA None None None

Sara Listed Ingredients: Methyl methacrylate

XII. PREPARATION INFORMATION

ISSUE DATE: 10/27/99 Rev. 1 - 12/04/02 PREPARED BY: Mary K. Robles

The data contained herein is based upon information that Pacer Technology believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.